


## STANDARD EXPANDED METAL

ALSO AVAILABLE IN ALUMINUM, STAINLESS AND GALVANIZED

Size (inches) & Style No.	Weight in Pounds per Hundred Sq. Ft.	Center to Center of Bond (inches)		Size of Openings (inches)		Size of Strands (inches)		Overall Thickness (inches)
		A	B	C	D	Width	Thickness	
		Width	Length	Width	Length	Width	Thickness	
3/16 # 24	50	0.200	0.50	0.166	0.437	0.050	0.024	0.086
# 22	62	0.200	0.50	0.166	0.437	0.050	0.030	0.088
# 20	75	0.200	0.50	0.166	0.437	0.050	0.036	0.090
1/4 # 20	86	0.255	1.00	0.172	0.719	0.073	0.036	0.125
# 18	114	0.255	1.00	0.172	0.719	0.073	0.048	0.125
1/2 # 20	43	0.500	1.20	0.438	0.938	0.072	0.036	0.124
# 18	70	0.500	1.20	0.438	0.938	0.088	0.048	0.155
# 16	86	0.500	1.20	0.375	0.938	0.086	0.060	0.157
# 13	147	0.500	1.20	0.313	0.938	0.096	0.092	0.182
3/4 # 16	54	0.923	2.00	0.813	1.750	0.099	0.060	0.186
# 13	80	0.923	2.00	0.750	1.688	0.096	0.092	0.195
# 10	120	0.923	2.00	0.750	1.625	0.144	0.092	0.282
# 9	180	0.923	2.00	0.688	1.563	0.148	0.134	0.300
1-1/2 # 18	20	1.330	3.00	1.313	2.625	0.067	0.048	0.140
# 16	40	1.330	3.00	1.250	2.625	0.107	0.060	0.211
# 13	60	1.330	3.00	1.188	2.500	0.104	0.092	0.215
# 10	79	1.330	3.00	1.188	2.500	0.137	0.092	0.289
# 9	120	1.330	3.00	1.125	2.375	0.142	0.134	0.295
# 6	250	1.330	3.00	1.000	2.313	0.201	0.198	0.425




## FLATTENED EXPANDED METAL

ALSO AVAILABLE IN ALUMINUM, STAINLESS AND GALVANIZED

Size (inches) & Style No.	Weight in Pounds per Hundred Sq. Ft.	Center to Center of Bond (inches)		Size of Openings (inches)		Size of Strands (inches)		Overall Thickness (inches)
		A	B	C	D	Width	Thickness	
		Width	Length	Width	Length	Width	Thickness	
3/16 # 24	48	0.200	0.52	0.085	0.459	0.057	0.019	0.019
# 22	60	0.200	0.52	0.085	0.459	0.057	0.024	0.024
# 20	72	0.200	0.52	0.085	0.459	0.057	0.029	0.029
1/4 # 20	83	0.255	1.03	0.094	0.688	0.086	0.030	0.030
# 18	111	0.255	1.03	0.094	0.688	0.086	0.040	0.040
1/2 # 20	40	0.500	1.26	0.375	1.000	0.070	0.029	0.029
# 18	66	0.500	1.26	0.281	1.000	0.109	0.039	0.039
# 16	82	0.500	1.26	0.250	1.000	0.103	0.050	0.050
# 13	140	0.500	1.26	0.250	1.000	0.122	0.070	0.070
3/4 # 16	51	0.923	2.10	0.750	1.750	0.115	0.048	0.048
# 14	63	0.923	2.12	0.688	1.813	0.119	0.061	0.061
# 13	75	0.923	2.10	0.688	1.782	0.119	0.070	0.070
# 9	171	0.923	2.12	0.563	1.688	0.164	0.120	0.120
1-1/2 # 16	38	1.330	3.20	1.063	2.750	0.123	0.048	0.048
# 14	46	1.330	3.20	1.063	2.750	0.138	0.060	0.060
# 13	57	1.330	3.20	1.063	2.750	0.138	0.070	0.070
# 9	111	1.330	3.20	1.000	2.563	0.175	0.110	0.110

STANDARD SHEET SIZE 4' X 8' - OTHER SIZES AVAILABLE



## EXPANDED METAL GRATING

ALSO AVAILABLE IN ALUMINUM, STAINLESS AND GALVANIZED


Style	Weight Pounds per in Hundred C.S.F.	Center to Center of Bond (inches)		Size of Openings (inches)		Size of Strands (inches)		Overall Thickness (inches)
		A	B	C	D	Width	Thickness	
		Width	Length	Width	Length			
3 lb.	300	1.335	5.33	0.938	3.438	0.261	0.183	0.500
3.14 lb.	314	2.000	6.00	1.625	4.875	0.308	0.250	0.562
4 lb.	400	1.335	5.33	0.938	3.438	0.297	0.215	0.625
4.27 lb.	427	1.412	4.00	1.000	2.875	0.297	0.250	0.625
5 lb.	500	1.333	5.33	0.813	3.375	0.327	0.250	0.625
6.25 lb.	625	1.412	5.33	0.813	3.375	0.347	0.312	0.750
7 lb.	700	1.412	5.33	0.813	3.375	0.388	0.312	0.750

Standard Sheet Size is 4' X 8'.

## BAR GRATING



Smooth-surface grating



Serrated-surface safety grating

GRATING AVAILABLE IN CARBON STEEL, ALUMINUM, STAINLESS AND FIBERGLASS

### Standard Sheet Sizes

2' & 3' wide


20' & 24' long

UNPAINTED OR GALVANIZED

### Standard Mesh Types

Type 19W4

(OTHER PATTERNS ARE AVAILABLE)



Lbs. Per Sq. Ft.			
Bearing Bars		Type 19W4	
3/4	x 1/8	4.0	
	x 3/16	5.6	
1	x 1/8	5.1	
	x 3/16	7.3	
1-1/4	x 1/8	6.1	
	x 3/16	8.9	

Lbs. Per Sq. Ft.			
Bearing Bars		Type 19W4	
1-1/2	x 1/8	7.3	
	x 3/16	10.6	
1-3/4	x 3/16	12.2	
2	x 3/16	13.9	
2-1/4	x 3/16	15.4	
2-1/2	x 3/16	17.1	

CUSTOM FABRICATED PIECES AVAILABLE – GRATING CLIPS STOCKED